



### KEY FEATURES

A unique 3D scanner designed for surveying professionals

Versatile to meet surveying needs in new and traditional applications

Complements other Trimble surveying systems in an Integrated Surveying™ solution

An important component of the Connected Survey Site



### THE TRIMBLE GX 3D SCANNER IS AN ADVANCED SURVEYING INSTRUMENT THAT USES HIGH SPEED LASER AND VIDEO TO CAPTURE COORDINATES AND IMAGE DATA

#### A SURVEYING WORKFLOW

The Trimble® GX™ 3D scanner is the first 3D laser scanner to offer a true surveying workflow. As such, the Trimble GX 3D scanner offers unique possibilities for surveying businesses: it opens doors to new opportunities and increases efficiency in traditional applications.

The surveying workflow is supported via features such as leveled station setup, flexible power supply options, and support for the rugged Trimble controllers popular among surveyors<sup>1</sup>. By thus “thinking like a surveyor” the Trimble GX 3D scanner offers significant benefits:

- Faster and fewer setups<sup>2</sup>
- Portability
- The ability to complement other surveying systems, such as the Trimble® S6 Total Station or Trimble® R8 GPS System

The Trimble GX 3D scanner enables surveying professionals to immediately incorporate 3D laser scanning into their business portfolio. With its short learning curve, the Trimble GX 3D scanner quickly provides optimal productivity gains and a fast return on investment.

#### EXCEPTIONAL VERSATILITY

The Trimble GX 3D scanner is remarkably versatile. Unique features allow the Trimble GX 3D scanner to adapt to each job's individual needs:

- The instrument suits multiple surveying applications. On many traditional surveying jobs, the instrument saves up to 80% of human resource costs, particularly when combined with Trimble® RealWorks Survey™ office software, which easily manages the enormous amounts of data in scan files.
- For some jobs you can set up on a known point or perform a traditional resection to determine the coordinates and orientation of the project. For other jobs, set up anywhere and take care of the coordinates later.

- Real-time autofocus helps collect highly precise data in a short time; a 360 servo-driven system scans indoors and outdoors.
- When a job requires less detail but longer range, the Trimble® OverScan™ technology boosts data acquisition capability up to 350 m. This feature allows fewer setups for shorter survey times, and the scanning of larger objects.

The versatility of the Trimble GX 3D scanner ensures that your investment is always working and always increasing your profitability.

#### THE ORIGINAL INTEGRATED SURVEYING SOLUTION AND BEYOND

Trimble's 3D scanning systems support Integrated Surveying and are an important part of Trimble's total surveying solution.

On a survey site you can combine surveying techniques to complete the requirements of a job. For example, set up a traverse using an optical solution such as the Trimble S6 Total Station, then on the control point, scan the survey area with high resolution using the Trimble GX 3D scanner.

In the office, RealWorks Survey imports scan files to a PC for manipulation. The software also supports processed GPS and optical data, so all your information from a survey site can be combined in one project file.

Whenever you're facing new surveying challenges, your partnership with Trimble places the right tools and techniques, including 3D scanning, at your fingertips. Each Trimble system seamlessly integrates via shared workflows and technologies, making your everyday job site a place where the whole is greater than the sum of its parts: Welcome to the Connected Survey Site.

<sup>1</sup> For example, the Trimble Recon® Controller, a Pocket PC device.  
<sup>2</sup> A typical setup takes less than 5 minutes.

# TRIMBLE GX 3D SCANNER

## PERFORMANCE

Range ..... standard: 200 m<sup>1</sup>; extended: 350 m (w/ OverScan)<sup>2</sup>  
Scanning speed ..... up to 5000 points per second  
Standard deviation<sup>3</sup> ..... 1.4 mm @ ≤50 m; 2.5 mm @ 100 m  
3.6 mm @ 150 m; 6.5 mm @ 200 m  
Single point accuracy ..... position = 12 mm @100 m;  
distance = 7 mm @ 100 m  
Hz angle = 12" (60 μrad); Vt angle = 14" (70 μrad)  
Target acquisition ..... std dev. <1 mm (Trimble targets)  
Modeled surface precision ..... ± 2 mm (depending on method)  
Leveling ..... circular level in tribrach: 8'  
Electronic dual axis level: resolution 6", range: ±14'  
Real-time automatic level compensation  
Data integrity ..... periodic zero index calibration  
real-time thermo-compensation  
Scan enhancement ..... atmospheric corrections (user definable)  
user-definable multishot averaging  
autofocus: user-controlled or auto-implementation  
Scan resolution ..... spot size: 3 mm @ 50 m  
Spot size with autofocus: ..... 0.3 mm @ 5 m; 0.9 mm @ 15 m;  
1.5 mm @ 25 m  
Point spacing: down to 3.2 mm @ 100 m  
(available 1.6 mm Vt = 18 pts/cm<sup>2</sup> / 105 points/sq.in)  
Scan row (hz): 200,000 points ; Scan row (vt): 65,536 points

## SYSTEM SPECIFICATIONS

Laser ..... type: pulsed 532 nm, green  
Class: IEC 60825-1 – Class 3R; 21 CFR §1041.10: Class 2  
Field of view ..... 360° x 60° continuous single scan  
Optics ..... patented scanning optical system  
Data transfer ..... USB link for available extensions  
Digital imaging ..... real-time integrated color video with  
5.5x optical zoom  
Status indicators ..... system ready, laser on, comm. status

## PHYSICAL

Servo-Driven 3D Laser  
Scanner ..... dimensions: 323 D x 343 W x 404 H mm  
weight: 12.2 kg (26.8 lb); power consumption: <100 W  
Power supply ..... super compact unit. AC 90–240 V, 50–60 Hz;  
DC 24 V nominal  
dimensions: 169 D x 65 W x 37.5 H mm;  
weight: 0.7 kg (1.5 lb)  
Transport case ..... airline checkable  
dimensions: 645 D x 490 W x 435 H mm;  
weight: 14.2 kg (32.4 lb)  
Environmental ..... operating temp: 0 °C to 40 °C ;  
storage temp: –20 °C to 50 °C  
light: fully operational under all light conditions  
sealing: IP53 (I.E.C.); shock: IEC 60721-3-2: 2M2 (scanner)  
2M3 (scanner in case) transportation compliant  
humidity: non-condensing atmosphere

Standard accessories ..... airline checkable transport case  
super-compact power supply unit with AC cables;  
Trimble tribrach; ethernet cable for connection of  
scanner to data collector; 50 adhesive flat targets;  
Trimble 3D Scanner Field Software installation kit  
Optional accessories ..... Trimble Recon controller with  
PocketScape field software  
Trimble 3D scanner backpack; car battery cable kit  
target kits; (planar, spherical); batteries

## FIELD SOFTWARE

PointScape field software for the Trimble GX 3D scanner runs on a Notebook PC. PocketScape field software runs on a Pocket PC device, such as the Trimble Recon controller. Both applications offer advanced scanning functionality:

### Survey workflow:

- Electronic level
- Dual axis compensation
- Atmospheric corrections
- Station setup and resection routines

### Framing tools:

- Rectangular framing
- Video zoom control
- Sphere, target and single point measurement

### Scanning options:

- Pre-set or custom scan settings
- Return intensity and colored point cloud
- Estimated scan time and resolution control

### Additionally, PointScape offers the following advanced features:

- Live video streaming
- Automatic panorama
- Automatic scan imaging
- Fast interactive framing on video, panorama or image
- Polygonal framing
- Multiple scan framing
- Automatic target and sphere recognition
- Real-time 3D visualization, pan and zoom, even while scanning
- Visualization of scanner location
- True color or intensity mapped point cloud display
- Simulated surface rendering and environmental lighting
- Measure and inverse computations

© 2005, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States Patent and Trademark Office and in other countries. GX, Integrated Surveying, OverScan, PointScape, PocketScape, RealWorks Survey, and TSC2 are trademarks of Trimble Navigation Limited. Recon is a registered trademark of Tripod Data Systems Inc. All other trademarks are the property of their respective owners. PN 022543-148 (10/05)

1 Measured to 90% white surface (albedo).

2 Data acquisition dependent on surface type.

3 Figures (typical values) given for standard data capture of four shots, on distance measurement.

Specifications subject to change without notice.

## NORTH AMERICA

Trimble Engineering &  
Construction Group  
5475 Kellenburger Road  
Dayton, Ohio 45424-1099 • USA  
800-538-7800 (Toll Free)  
+1-937-245-5154 Phone  
+1-937-233-9441 Fax

## EUROPE

Trimble GmbH  
Am Prime Parc 11  
65479 Raunheim • GERMANY  
+49-6142-2100-0 Phone  
+49-6142-2100-550 Fax

## ASIA-PACIFIC

Trimble Navigation  
Singapore Pty Limited  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269 • SINGAPORE  
+65-6348-2212 Phone  
+65-6348-2232 Fax

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER



www.trimble.com