

Spectra Precision Laser LL500



Rugged, Reliable Laser Leveling Systems

Setting the Industry Standard

Accurate, stable and very reliable, the Spectra Precision™ Laser LL500 is the ideal one-person leveling system for a range of everyday elevation measurements on the construction site.

Designed for use on the jobsite, and reliability even in the harshest of conditions, today more contractors around the world use Spectra Precision Lasers to increase productivity and profitability.

One Laser Levels Your Entire Work Area

The LL500 transmitter sends a continuous, self-leveled 360-degree laser reference over a work area, up to a 500-meter (1,600-foot) diameter.

With the LL500, you can perform any two-person leveling task with just one person. Simply set up the laser transmitter anywhere on your job site; it transmits a laser beam to provide an elevation reference that can be picked up by one or more laser receivers, including our innovative HR500 or CR600, whether they are handheld, attached to a grade rod or mounted on a machine.

HR500 Receiver

The Spectra Precision Laser HR500 receiver is ideal for use with the LL500 transmitter. This flexible and highly innovative receiver can be used either as a handheld or rod mounted. The HR500 features a fully waterproof magnesium housing that is both lightweight and capable of surviving a drop of up to 3 meters (10 feet) onto concrete. The highly visible LED display and dual-sided laser reception allow you to work anywhere.

CR600 Receiver

Another receiver option is the Spectra Precision Laser CR600. In addition to handheld and rod-



mounted capabilities, the CR600 can be used as a machine-mounted receiver with 270-degree reception and a highly visible display for use on a backhoe, small excavator or skid steer. Improving accuracy, safety and efficiency, the



CR600 delivers grade information to the operator right in the cab.

LL500 Benefits

- Meets your toughest accuracy requirements.
- Reduces the amount of time required for each grade shot, so more grade shots are taken for increased accuracy.
- Eliminates rework caused by miscommunication or out-of-level instruments with built-in out-of-level warning and shut-off.
- Immediately locates the laser plane with the visible spotting beam.



LL500 Applications

- Checking and adjusting elevations
- Taking grade shots
- Excavating cutting depth
- Basement excavation
- Digging septic tanks
- Checking foundations
- Digging footings
- Setting forms
- Checking sub-base materials
- Screeding concrete
- Slope on grade



Spectra Precision Laser LL500

Rugged, Reliable Laser Leveling Systems



LL500 Laser Specifications

Self-Leveling Range ± 11 arc minutes
 Compensation Type Wire Hung,
 Air Damped
 Accuracy ± 10 arc seconds,
 1.5 mm at 30 m (1/16 in at 100 ft)
 Laser Type 670 nm visible, Class II
 Machine Control Compatible Yes
 Warranty 2 Years Use-and-Abuse
 Solar Power Option Yes
 Battery Life 20°C (68°F) . . 4 D-Cell Alkaline
 80 hrs, Ni-Cad (4.4 Ahr) 27 hrs
 Operating Diameter 500 m (1,600 ft)
 Operating Temperature . . . -20°C to 50°C
 (-4°F to 122°F)
 Weight 3.6 kg (8 lbs)
 Tripod Mount 5/8 in x 11

HR500 Receiver Specifications

Five On-Grade Sensitivities . . . Ultra Fine 0.1 mm (0.004 in)
 Super Fine 1.0 mm (1/32 in)
 Fine 1.5 mm (1/16 in)
 Medium 3 mm (1/8 in)
 Coarse 6 mm (1/4 in)
 Operating Temperature -20°C to 50°C (-4°F to 122°F)
 Battery Life (AA-2) 100 hours at normal operation
 Auto Shut-Off 30 minutes
 Weight 0.27 kg (9 1/2 oz)
 Reception Angle 180 degrees
 Out-of-level warning Yes
 Waterproof 100%

CR600 Receiver Specifications

Seven On-Grade Sensitivities . . Ultra Fine 0.1 mm (0.004 in)
 Super Fine 1.0 mm (1/32 in)
 Fine 1.5 mm (1/16 in)
 Medium 3 mm (1/8 in)
 Coarse 6 mm (1/4 in)
 Machine Fine 10 mm (3/8 in)
 Machine Coarse 25 mm (1 in)
 Operating Temperature . . . -20°C
 to 50°C (-4°F to 122°F)
 Battery Life (AA-3) . . 100 hours
 at normal operation
 Auto Shut-Off 30 minutes
 Weight 0.5 kg (1.1 lb)
 Reception Angle . . 270 degrees
 Out-of-level warning Yes
 Waterproof 100%

HR500 and CR600 Receiver Features

- 15-channel linear LCD display allows for fast, accurate readings and easy fixed offsets.
- Simultaneous 5-channel green and red LED display ensures that information can be read even in poor light, over long distances, and at an angle.
- Rugged and waterproof magnesium housing can survive a drop of up to 3 m (10 ft) onto concrete.
- Dual-sided photocells let you receive the beam from multiple directions and maintain convenient control and view of the receiver.
- Wraparound receiver cells with continuous pickup through an operating range of 270° mean less setups and improved productivity, especially for machine applications.



HR500



CR600

YOUR LOCAL TRIMBLE OFFICE OR REPRESENTATIVE



North America

Trimble Engineering and Construction Division
 5475 Kellenburger Road • Dayton, Ohio 45424-1099
 800-538-7800 • 937-233-8921 • 937-233-9441 Fax

Europe

Trimble GmbH • Am Prime Parc 11,
 65479 Raunheim, Germany
 +49-6142-21000 • +49-6142-21-00-550 Fax

Asia-Pacific

Trimble Navigation Australia
 Pty Limited
 Level 1/123 Gotha Street,
 Fortitude Valley, QLD 4006, Australia
 +61-7-3216-0044
 +61-7-3216-0088 FAX

WWW.TRIMBLE.COM

